

Card
Printer

DC-7600 & DC-5100

Fast and
reliable



HIGHLIGHTS AT A GLANCE:

- In connection with DC-7600 single and double-sided lamination
- 2-line LCD display
- Suitable for laminates of 0.6 mil or 1.0 mil
- Processing speed up to 35 mm / sec.

DASCOM[®]
SOLUTIONS FOR BUSINESS PRINTING

DC-5100

Housing opens upwards

Easy change of the laminate rolls

User-friendly display

Robust housing design

RFID tag for laminate

TECHNICAL DATA

Lamination method	Thermal direct
Lamination modus	Single side; Double side (only in combination with DC-7600)
Lamination speed	5 - 35 mm/sec.
Card thickness	0,48 - 1,1 mm (20 - 50 mil)
Card types	PVC, 85,6 x 53,98 mm (ISO ID-1/CR-80 format)
Card feeder	Manual insertion for single card or automatic feeding in combination with DC-7600
Interface	USB (2.0), Ethernet (10/100)
Security	RFID protected laminate roll
Consumables	Patches (200 pcs.; 0,6 mil thickness)
Sensor	Black Mark
Weight	8,3 kg
Dimension	220 x 270 x 370 mm (B x T x H)
Voltage	100 - 240 V AC - 50/60 Hz
Power consumption	96 W
Temperature	Laminating: +15° to +30° C; 35 - 70% rel. humidity Storing: +5° C to +45° C; 20 - 90% rel. humidity



The DASCOM DC-5100 can be used with different patches and thin fils with a thisckness up to 1,0 mil.



CHINA
DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Center
264-298 Castle Peak Road | Tuen Wan, N. T.
Hong-Kong | P.R. CHINA
info.cn@dascom.com | www.dascom.com

APAC
DASCOM AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building
Singapore 609601
sales@dascom.com.sg | www.dascom.com.sg

AMERICAS
DASCOM Americas.
34 Lakeview Court | Verona
Virginia, 24482 | USA
info.us@dascom.com | www.dascomamericas.com

EMEA
DASCOM Europe GmbH.
Heuweg 3
89079 Ulm | GERMANY
info.de@dascom.com | www.dascomeuope.de

All company and product names are trademark of theri respective owner. Copyright © 2024 DASCOM. Specification are subject to change without notice.
Subject to modification, of error or misprint.

DASCOM