



TL-200

Indispensable in many places



HIGHLIGHTS AT A GLANCE:

- Easy and Quick media loading
- USB interface standard
Ethernet interface optional
- Supports ZPL and EPL emulation
- Small footprint

TL-200

Tally Dascom's TL-200 thermal transfer printer offers reliability, precision and performance in a compact size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use print mechanism ensures quick media loading.

The TL-200 is easily integrated into existing systems as there are USB and Ethernet interfaces also available.

TECHNICAL DATA

Print Speed	5 ips (127 mm/Sek.)
Print Width	4" (104 mm)
Print Method	Direct Thermal
Resolution	203 dpi
Fonts	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
Print head Lifetime	30 km or 6 months
Memory	8 MB Flash, 32 MB SDRAM
Interfaces Standard	USB (2.0 Full Speed)
Interfaces Optional	Ethernet (10/100)
Emulations	ZPLII, EPL, TSPL
Consumables	Direct Thermal paper and labels
Media	Width: 25.4 - 118 mm; Thickness: 0.08 - 0.254 mm Core diameter: 1", 1.5" or 3" (25.4 mm, 37 mm or 76.2 mm); Outside diameter: 5" (130 mm)
Sensors	Cover open, paper end, label, paper tear, black mark
Barcode	1D: ANSI Codabar, CODABLOCK, Code 11, Code 128 (Subsets A, B, and C), Code 39, Code 93, EAN-13, EAN-8, GS1 Databar, Industrial 2 of 5, Interleaved 2 of 5, Plessey, Standard 2 of 5, UPC-A, UPC-E 2D: MicroPDF417, PDF 417, UPS MaxiCode, QR Code, Data Matrix
Physical Weight	1.8 kg
Physical Size	184 × 247 × 170 mm (W × D × H)
Power Voltage	100 - 240 V AC - 50/60 Hz
Temperature	+5°C to +40°C
Humidity	30% to 80% (non condensing)
Print Volume	up to 300 m/day
Printer Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022
Options	Ethernet interface
Warranty	For more details please contact your local dealer

Configurations:

- **TL-200** Standard Product (USB only)
- **TL-200 Eth** Model with USB & Ethernet interface

CHINA

Jiangmen Dascom Computer Peripherals Co., Ltd.
No.399, Jinxing Road | Jianghai District | Jiangmen City
Guangdong Province | CHINA
Tel.: +86 0750-3868008 | Fax: +86 0750-3868011
info.cn@dascom.com | www.dascom.com

APAC

DASCOM AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building
Singapore 609601
Tel.: +65 6760 8833 | Fax: +65 67601066
info.sg@dascom.com | www.dascom.com.sg

AMERICAS

DASCOM Americas
34 Lakeview Court | Verona | Virginia, 24482 | USA
Tel.: +1 (877) 434-1377
info.us@dascom.com | www.dascomamericas.com

EMEA

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info.de@dascom.com | www.dascomeurope.de