

# DP-530/DP-530L



**Tally**  
**DASCOM**

With the Tally Dascom DP-530 series you can concentrate on your job and not on the printer.

Although the printer is up to 10% smaller and 40% lighter than comparable models, it makes no compromises. A variety of interfaces and emulations allow the use of DP-530/DP-530L in different environments.

### Highlights at a glance:

- Easy-to-read control panel and simple drop-in paper loading
- Simple drop-in paper loading
- High-speed signature printing and extensive font and graphic capabilities
- Popular printer emulations provide compatibility

Whether water, dust or vibrations, this printer operates reliably. Whether in the basic variant DP-530 for receipt documents or in the label version as DP 530L.

Thanks to different holders, the printer can easily install on mobile dollies or in vehicles.

#### Configurations:

- **DP-530** Standard model
- **DP-530 BT** Model with Bluetooth
- **DP-530 WiFi** Model with WiFi

- **DP-530L** Label model
- **DP-530L BT** Model with Bluetooth
- **DP-530L WiFi** Model with WiFi

# DP-530/DP-530L

<b>Print Method</b>	Direct thermal printing
<b>Resolution</b>	203 dpi (8 Dots/mm)
<b>Print Speed</b>	Up to 5 inch/sec.
<b>Barcodes</b>	82 different versions
<b>Download</b>	Graphics and logos
<b>Standard Connectivity</b>	USB
<b>Optional Connectivity</b>	Bluetooth (2.0) and WiFi (802.11 b/g/n)
<b>Bluetooth</b>	Compatible Bluetooth 2.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE
<b>Emulations</b>	Zebra CPCP and ZPL, EPL, ESC/POS, O'Neil, Printek
<b>Printer Drivers</b>	Windows 7/8; SDK for Windows CE/Mobile and Android; iOS unde preparation
<b>Printer Roll Size</b>	max. diameter 2" (5 cm) for DP-530 and 2,6" (6,6 cm= for DP-530L; Width 2,26 to 3,125" (5,7 to 8,0 cm)
<b>Roll Capacity</b>	approx. 28 m (equal 188 pcs. 6"-receipts) for DP-530 approx. 52 m (equal 346 pcs. 6"-labels) for DP-530L
<b>Roll Diameter</b>	0,75" (1,9 cm)
<b>Battery</b>	Rechargeable 3-cell Lithium Ion (2.950 mAH)
<b>Battery lifetime</b>	More than 4.000" (101 m) /8 hours shift without WiFi
<b>Charging</b>	2 hours
<b>Weight</b>	0,57 kg incl. battery
<b>Dimensions</b>	117 x 155 x 69 mm (W x D x H) for DP-530 117 x 155 x 79 mm (W x D x H) for DP-530L
<b>Power Voltage</b>	12/24 V
<b>Temperature</b>	-20° C to 50° C (operating), -20° C to 60° C (storing)
<b>Humidity</b>	10% to 90%
<b>MTBF</b>	10.000 hours
<b>Approvals</b>	CE, FCC Class B, UL, RoHS, eMark



Cigarette lighter  
for vehicle



Mounting plate



Mounting plate  
with ball



Bracket  
with round plate



Bracket  
with pole

**CHINA**  
**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Center  
264-298 Castle Peak Road | Tuen Wan, N. T.  
Hong-Kong | P.R. CHINA  
info.cn@dascom.com | www.dascom.com

**APAC**  
**DASCOM AP Pte. Ltd.**  
2 Jurong East Street 21 | # 05-42, IMM Building  
Singapore 609601  
sales@dascom.com.sg | www.dascom.com.sg

**AMERICAS**  
**DASCOM Americas.**  
34 Lakeview Court | Verona  
Virginia, 24482 | USA  
info.us@dascom.com | www.dascomamericas.com

**EMEA**  
**DASCOM Europe GmbH.**  
Heuweg 3  
89079 Ulm | GERMANY  
info.de@dascom.com | www.dascomeuope.de