

DK-670
Over-the-Edge
Kiosk printing



HIGHLIGHTS AT A GLANCE:

- High resolution printing with 600 dpi
- High productivity due to high speed printing
- Over-the-Edge full card printing
- Variety of smart card encoders

DK-670

Retransfer print technology is the next level of Direct-to-Card technology. First, the image is printed on a film, then the image is transferred from film to the card. This technique is suitable for edge-to-edge printing, heavy duty printing, improves reliability and thus suitable for a large variety of card types, such as:

- Travel ID cards
- Identity cards
- Student cards
- Entry permit cards
- High quality card applications
- Finance cards
- Resident cards
- Driving Licenses

TECHNICAL DATA

Print Method	Colour dye sublimation retransfer technology
Resolution	600 dpi
Print Capability	Single Side, Double Side, Over-the-Edge, photo quality image colour
Print Speed	30 sec.
Interfaces	USB (2.0), Ethernet (10/100) 2x RS-232C for extended users), USB-HUB
Card Thickness	0,48 - 1,10 mm
Security Features	RFID ribbon, card feeder lock, custom watermarks (BMP)
Card Loading	Auto card feeder for 250 cards (0,76 mm thickness) Manual feed: single card
Card Reject	Reject box for 140 cards (0,76 mm thickness)
Card Output	Left in and left out, left in and right out, right in and right out, right in and left out
Card Types	PVC, PET, PET-G 85,6 x 53,98 mm (ISO CR-80/ISO7810 size)
Consumables	Ribbon YMCK (500 Images), Ribbon YMCKH (400 Images), Ribbon YMCKK (400 Images), Ribbon YMCKI (400 Images), Ribbon YMCKSI (350 Images), Transfer Film YMCK (500 Images)
Cleaning Set	Cleaning Card Cleaning Roller
Physical Weight	18,9 kg (Cleaninf module included)
Physical Size	370 x 305 x 358 mm (W x D x H) (Cleaning module included) 340 x 305 x 358 mm (W x D x H) (Without cleaning module)
Power Voltage	Auto wide ranging, 90 - 264 V AC - 50/60 Hz
Power Consumption	15 W in saving mode
Temperature	10° - 35° C Operating -20° - 60° C Storage
Humidity	20 - 80% Operating 0 - 90% Storage
Options	3-in-1 Encoder, Contact Encoder, Contactless Encoder External cleaning module
Driver	Windows XP/7/8/10(32 and 64 bit)
Warranty	For more details please contact your local dealer

CHINA

Jiangmen Dascom Computer Peripherals Co., Ltd.
No.399,Jinxing Road | Jianghai District | Jiangmen City
Guangdong Province | CHINA
Tel.: +86 0750-3868008 | Fax: +86 0750-3868011
info.cn@dascom.com | www.dascom.com

APAC

DASCOM AP Pte. Ltd.
2 Jurong East Street 21 | # 05-42, IMM Building
Singapore 609601
Tel.: +65 6760 8833 | Fax: +65 67601066
info.sg@dascom.com | www.dascom.com.sg

AMERICAS

DASCOM Americas
34 Lakeview Court | Verona | Virginia, 24482 | USA
Tel.: +1 (877) 434-1377
info.us@dascom.com | www.dascomamericas.com

EMEA

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info.de@dascom.com | www.dascomeurope.de