

# 2610+

High performance at low cost



## HIGHLIGHTS AT A GLANCE:

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- SB Host interface for easy firmware-update
- • User-friendly, backlit illuminated LC display

# 2610+

The new Tally Dascom 2610+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 15 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

## TECHNICAL DATA

<b>Print speed</b>	Fastest Speed: 683 cps Character density 10 / 12 / 15 cpi <i>HS Draft</i> 600 / 683 / 683 cps <i>Draft</i> 513 / 513 / 513 cps <i>NLQ</i> 228 / 273 / 171 cps <i>LQ</i> 114 / 137 / 171 cps
<b>Resolution</b>	Up to 360 x 360 dpi
<b>Throughput</b> (ECMA 132)	457 pages per hour
<b>Character density</b>	10, 12, 15, 17.1, 20 cpi
<b>Line density</b>	2, 3, 4, 6, 8, 12 lpi
<b>Print head lifetime</b>	500 Mio. impact per wire
<b>RAM</b>	256 kB
<b>Interface Standard</b>	Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6) USB Host
<b>Interface Optional</b>	Serial RS-232
<b>Administration</b>	Tally WebPanel via Ethernet; Config-Tool via USB/Parallel
<b>Emulations Standard</b>	IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9-Nadel Emulation <b>LA Upgrade Kit:</b> DEC PPL2
<b>Fonts</b>	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing
<b>Consumables</b>	Ribbon: 15 Mio. characters
<b>Paper handling Standard</b>	One tractor usable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off
<b>Paper handling Optional</b>	Additional push tractor (rear)
<b>Copies</b>	Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 5 copies; Cut sheet: 1 original + 5 copies
<b>Paper types</b>	Cut sheets, continuous forms, multi-part forms
<b>Paper weight</b>	60-120 g/m <sup>2</sup>
<b>Paper format</b>	Width: 76 to 420 mm; Length: 76 to 599 mm
<b>Weight</b>	10,6 kg
<b>Dimensions</b>	600 x 265 x 200 mm (W x D x H)
<b>Noise</b>	<53 dB(A)
<b>Voltage</b>	100 - 240 V autosensing
<b>Power consumption</b>	60 Watt printing; <3 W Sleep Mode
<b>Temperature</b>	+10° to +40° C; 10% to 85% rel. humidity
<b>Print volume</b>	20.000 pages per month
<b>MTBF</b>	25.000 hours @20% duty cycle
<b>Driver</b>	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; SAP
<b>Warranty</b>	For more details please contact your local dealer

**Configuration:** 2610+ (Standard model)

### CHINA

Jiangmen Dascom Computer Peripherals Co., Ltd.  
No.399,Jinxing Road | Jianghai District | Jiangmen City  
Guangdong Province | CHINA  
Tel.: +86 0750-3868008 | Fax: +86 0750-3868011  
info.cn@dascom.com | www.dascom.com

### APAC

DASCOM AP Pte. Ltd.  
2 Jurong East Street 21 | # 05-42, IMM Building  
Singapore 609601  
Tel.: +65 6760 8833 | Fax: +65 67601066  
info.sg@dascom.com | www.dascom.com.sg

### AMERICAS

DASCOM Americas  
34 Lakeview Court | Verona | Virginia, 24482 | USA  
Tel.: +1 (877) 434-1377  
info.us@dascom.com | www.dascomamericas.com

### EMEA

DASCOM Europe GmbH  
Heuweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info.de@dascom.com | www.dascomeurope.de